

HARBACH ELECTRONICS/PETER W. DAHL AMATEUR TRANSFORMER DATABASE

H

HALLICRAFTERS FPM-300-MKII POWER TRANSFORMER
CORE) EI-150 X 2.5 STYLE #) 06 E-I LAMINATED CORE
PR) PRI "1" 117/234 PRI "2" 18.7 VCT
S1) 215 VAC @ 250MA
S2) 320 VAC @ 250MA
S3) 12 VAC @ 1A
S4) 6.3-0-103 VAC @ 4A-0-100MA
DM) HT = 3.688 WT = 4.500 DT = 3.750 MD = 3.000 MW = 3.750 WEIGHT) 12 LBS

HALLICRAFTERS HT-32 DC CHOKE L-25, P/N 056-300259
CORE) EI-087 X 1 STYLE #) 01 E-I LAMINATED CORE
PR) 9.0 HY @ 135MA DC
DM) HT = 2.188 WT = 2.625 DT = 2.103 MD = 2.000 MW = 2.188 WEIGHT) 2 LBS

HALLICRAFTERS HT-32 MARK I T4 MAIN POWER TRANSFORMER
CORE) EI-175 X 3 STYLE #) 06 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 880-270-90-0-270-880 VAC @ 300MA CCS
S2) 6.3 VAC @ 11A CCS
S3) 5.0 VAC @ 3A CCS
S4) 5.0 VAC @ 3A CCS
DM) HT = 4.250 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 19 LBS

HALLICRAFTERS HT-32A POWER MAIN POWER TRANSFORMER T4
CORE) EI-175 X 3 29GA M6X STYLE #) 06 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 880-270-140-0-270-880 VAC @ 300MA CCS
S2) 6.3 VAC @ 11A CCS
S3) 5.0 VAC @ 3A CCS
S4) 5.0 VAC @ 3A CCS
DM) HT = 4.250 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 19 LBS

HALLICRAFTERS HT-32B POWER MAIN POWER TRANSFORMER T103
CORE) EI-175 X 3 STYLE #) 06 E-I LAMINATED CORE
PR) 0-75-117 VAC 60 HZ 1 PH
S1) 880-270-140-0-270-880 VAC @ 300MA CCS
S2) 6.3 VAC @ 11A CCS
S3) 5.0 VAC @ 3A CCS
S4) 5.0 VAC @ 3A CCS
DM) HT = 4.250 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 19 LBS

HALLICRAFTERS HT-33 SPECIAL
CORE) EI-212 X 4 STYLE #) 04 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 4500 VCT @ 500MA CCS
DM) HT = 6.375 WT = 5.313 DT = 6.678 MD = 5.250 MW = 4.250 WEIGHT) 38 LBS

HALLICRAFTERS HT-33A PLATE EXACT REPLACEMENT (2700 VDC FOR PL-172)
CORE) EI-212 X 4.625 STYLE #) 04 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 6000 VCT @ 0.350A CCS (FWCT LC RECT)
DM) HT = 6.375 WT = 5.313 DT = 7.303 MD = 5.750 MW = 4.250 WEIGHT) 43 LBS

HALLICRAFTERS HT-33A/B FIL HT-33A OR HT-33B FILAMENT TRANSFORMER
CORE) EI-137 X 1.375 STYLE #) 05 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 350 VCT @ 100MA CCS
S2) 6.0 VAC @ 7.8A CCS
S3) 2.5 VAC @ 10A CCS (10 KVDC INS)
DM) HT = 4.125 WT = 3.438 DT = 3.750 MD = 2.375 MW = 2.750 WEIGHT) 6 LBS

HALLICRAFTERS HT-33B CHOKE SWINGING CHOKE FOR HV POWER SUPPLY (L3)
CORE) EI-175 X 2.5 STYLE #) 05 E-I LAMINATED CORE
PR) 55 HY @ 0.050A TO 8 HY @ 0.4A DC
DM) HT = 5.250 WT = 4.375 DT = 4.705 MD = 3.625 MW = 3.500 WEIGHT) 17 LBS

HALLICRAFTERS HT-33B PLATE EXACT REPLACEMENT (2700 VDC FOR PL-172)
CORE) EI-212 X 4.625 STYLE #) 04 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 6000 VCT @ 0.350A CCS (FWCT LC RECT)
DM) HT = 6.375 WT = 5.313 DT = 7.303 MD = 5.750 MW = 4.250 WEIGHT) 43 LBS

HALLICRAFTERS HT-33B PLATE I EXACT REPLACEMENT (2700 VDC FOR PL-172)
CORE) EI-212 X 4.625 STYLE #) 04 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 6000 VCT @ 0.350A CCS (FWCT LC RECT)
DM) HT = 6.375 WT = 5.313 DT = 7.303 MD = 5.750 MW = 4.250 WEIGHT) 43 LBS

HALLICRAFTERS HT-37 POWER MAIN POWER TRANSFORMER
CORE) EI-175 X 3 STYLE #) 06 E-I LAMINATED CORE
PR) 0-75-117 VAC 60 HZ 1 PH
S1) 880-270-140-0-270-880 VAC @ 300MA CCS
S2) 6.3 VAC @ 11A CCS
S3) 5.0 VAC @ 3A CCS
S4) 5.0 VAC @ 3A CCS
DM) HT = 4.250 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 19 LBS

HALLICRAFTERS HT-41 PLATE 1800 VDC @ 400 MA CCS FROM FWCT RECT
CORE) EI-212 X 4 STYLE #) 02 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 4200 VCT @ 400MA CCS (FWCT)
DM) HT = 5.312 WT = 6.375 DT = 6.678 MD = 5.250 MW = 5.312 WEIGHT) 38 LBS

HALLICRAFTERS HT-41 SWG CHOK SWINGING CHOKE
CORE) EI-150 X 2.5" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 25 HY @ 50 MA TO 5 HY @ 450MA DC
DM) HT = 4.500 WT = 3.750 DT = 4.875 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

HALLICRAFTERS HT-45 BRIDGE
CORE) A-516 C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 3500 VRMS @ 0.5A CCS
DM) HT = 8.375 WT = 6.578 DT = 5.625 MD = 4.500 MW = 6.000 WEIGHT) 33 LBS

HALLICRAFTERS HT-45 CHOKE HT-45 MARK II-A SWINGING CHOKE (L1)
CORE) EI-150 X 2 STYLE #) 04 E-I LAMINATED CORE
PR) 16 HY @ 50 MA TO 4 HY @ 350MA DC
DM) HT = 4.500 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

HALLICRAFTERS HT-45 PLATE TO PRODUCE 2700 VDC @ 400 MA CCS
CORE) A-516 C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 6000 VCT @ 400MA CCS (FWCT)
DM) HT = 8.375 WT = 6.578 DT = 5.625 MD = 4.500 MW = 6.000 WEIGHT) 33 LBS

HALLICRAFTERS P-20A PLATE
CORE) EI-212 X 3.5 STYLE #) 05 E-I LAMINATED CORE
PR) 115 VAC 60 HZ-STATIC SHIELD 1 PH
S1) 3300 VCT @ 350MA DC
DM) HT = 6.375 WT = 5.313 DT = 6.178 MD = 4.750 MW = 4.250 WEIGHT) 34 LBS

HALLICRAFTERS P-20A POWER
CORE) EI-150 X 2 STYLE #) 02 E-I LAMINATED CORE
PR) 110/220 VAC 50/60 HZ W/+OR-10% BUCK 1 PH
S1) 46 VCT @ 8A CCS 10% BUCK-BOOST
DM) HT = 3.750 WT = 4.500 DT = 3.890 MD = 3.000 MW = 3.750 WEIGHT) 10 LBS

HALLICRAFTERS P-26 POWER
CORE) EI-175 X 2 STYLE #) 05 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 860-230-0-130-230-860 @ 300MA
DM) HT = 5.250 WT = 4.375 DT = 4.205 MD = 3.125 MW = 3.500 WEIGHT) 14 LBS

HALLICRAFTERS PS-150-120 POWER TRANSFORMER FOR HT-44 POWER SUPPLY
CORE) EI-175 X 2 STYLE #) 06 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 630 VCT @ 450MA CCS
S2) 120 VAC @ 20MA CCS
S3) 12.6 VAC @ 4.5A CCS
DM) HT = 4.125 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 14 LBS

HALLICRAFTERS PS-500A-AC POWER TRANSFORMER, T201
CORE) EI-175 X 2.5 STYLE #) 06 E-I LAMINATED CORE
PR) 117/234 VAC 60 HZ 1 PH
S1) 600 VCT @ 0.6A CCS
S2) 135 VAC @ 0.05A CCS
S3) 12.6 VAC @ 5.0A CCS
DM) HT = 3.750 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 17 LBS

HALLICRAFTERS SR-2000 PLATE TRANSFORMER (PLATE & SCREEN) VOLTAGES
CORE) EI-175 X 4" 29GA MX6 STYLE #) 02 E-I LAMINATED CORE
PR) 117/234 VAC HI-LO TAPS 60 HZ 1 PH
S1) 1080 VRMS @ 0.91A CCS
S2) 450 VRMS @ 0.070A CCS
DM) HT = 4.375 WT = 5.250 DT = 6.205 MD = 5.125 MW = 4.375 WEIGHT) 25 LBS

HALLICRAFTERS SR-2000 SCREEN CHOKE L301
CORE) EI-75 SQ. STYLE #) 1 E-I LAMINATED CORE
PR) 15 HY @ 100MA
DM) HT = 1.925 WT = 2.316 DT = 1.875 MD = 0.000 MW = 2.813 WEIGHT) 1 LBS

HALLICRAFTERS SX-117 POWER XFMR FOR SX-117 RECEIVER
CORE) EI-100 X 1.25" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 360 VCT @ 0.1A CCS
S2) 6.3 VAC @ 6A CCS
DM) HT = 3.000 WT = 2.500 DT = 2.875 MD = 2.250 MW = 2.000 WEIGHT) 3 LBS

HALLICRAFTERS SX-28 AUDIO OUTPUT

CORE) EI-075 X .75 STYLE #) 01 E-I LAMINATED CORE

PR) 9K OHMS P-P

S1) 100/500/5000 OHMS

DM) HT = 1.955 WT = 2.330 DT = 1.575 MD = 0.000 MW = 2.813 WEIGHT) 1 LBS

HALLICRAFTERS SX-62A POWER T30, MAIN POWER TRANSFORMER

CORE) EI-150 X 2 STYLE #) 06 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 520 VCT @ 0.3A CCS

S2) 5.0 VAC @ 3.0A CCS

S3) 6.3 VAC @ 8.0A CCS

DM) HT = 3.188 WT = 4.500 DT = 3.750 MD = 3.000 MW = 3.750 WEIGHT) 10 LBS

HAMMARLUND HQ-100C POWER

CORE) EI-112 X 1.5 29M6RH STYLE #) 06 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 500 VCT @ 90MA CCS

S2) 5.0 VAC @ 2A CCS S3) 6.3 VAC @ 3A CCS

DM) HT = 2.434 WT = 3.375 DT = 2.813 MD = 2.250 MW = 2.813 WEIGHT) 4 LBS

HAMMARLUND HX-50 POWER MAIN POWER XFMR, P/N 26726-1 (6DQ5 PA)

CORE) EI-150 X 2.5" 29GM6R STYLE #) 06 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 700-425-20-0-425-700 VAC @ 200MA CCS

S2) 5.0 VAC @ 3A CCS

S3) 6.3 VAC @ 10A CCS

DM) HT = 4.500 WT = 3.750 DT = 4.390 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

HAMMARLUND HX-500 POWER T16 MAIN POWER XFMR, P/N K42351-1

CORE) EI-150 X 3 STYLE #) 06 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 900-320-110-0-320-900 VAC @ 175MA CCS

S2) 12.6 VAC @ 1.2A CCS (5 KV TEST)

S3) 6.3 VAC @ 10A CCS

DM) HT = 4.188 WT = 4.500 DT = 3.750 MD = 3.000 MW = 3.750 WEIGHT) 14 LBS

HAMMARLUND HXL-1 PLATE HIPERSIL REPLACEMENT TRANSFORMER

CORE) A-393 C-CORE STYLE #) 10 HIPERSIL C-CORE

PR) 115/230 VAC 60 HZ 1 PH

S1) 900 VAC @ 1.0A CCS

DM) HT = 6.000 WT = 6.325 DT = 6.281 MD = 3.625 MW = 4.000 WEIGHT) 23 LBS

HEATH AT-1 POWER XFMR P/N 54-21

CORE) EI-125 X 1.25" 29GA M6X STYLE #) 05 E-I LAMINATED CORE

PR) 115 VAC 60 HZ 1 PH

S1) 860 VCT @ 0.1A CCS (FWCT)

S2) 5.0 VAC @ 3A CCS

S3) 6.3 VAC @ 2A CCS

DM) HT = 3.750 WT = 3.125 DT = 3.375 MD = 2.250 MW = 2.500 WEIGHT) 4 LBS

HEATH BR-2

CORE) EI-100 X 1.25 STYLE #) 05 E-I LAMINATED CORE

PR) 117 VAC 60 HZ 1 PH

S1) 440 VCT @ 75MA

S2) 5 VAC @ 2A

S3) 12.6 VAC @ 0.6A

DM) HT = 3.000 WT = 2.500 DT = 2.510 MD = 2.250 MW = 2.000 WEIGHT) 3 LBS

HEATH CHIPPEWA PLATE XFMR REPLACES BASLER ELECTRIC P/N BE-7129
CORE) A-0516/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 7000 VCT @ 0.5A ICAS (FWCT)
DM) HT = 9.275 WT = 6.578 DT = 5.625 MD = 4.500 MW = 6.000 WEIGHT) 33 LBS

HEATH DX-100 DRIVER AUDIO DRIVER, P/N 51-23
CORE) EI-050 X .625 STYLE #) 03 E-I LAMINATED CORE
PR) 2500 OHMS @ 20MA DC
S1) 2000 OHMS CT
DM) HT = 1.705 WT = 1.393 DT = 1.313 MD = 0.000 MW = 1.719 WEIGHT) LBS

HEATH DX-100 LOW VOLTAGE HEATH P/N 54-31
CORE) EI-150 X 2 STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 317-60-0-60-317 VAC @ 250MA CCS
S2) 5 VAC @ 4A (3 KV INSULATION)
S3) 5 VAC @ 2A
S4) 12.6 VCT @ 4A
DM) HT = 4.500 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

HEATH DX-100 MOD DX-100 MODULATION TRANSFORMER
CORE) EI-112 X 1.5 STYLE #) 05 E-I LAMINATED CORE
PR) 8000 OHMS PP C.T. 845 VCT
S1) 500/2800 O @ 250MA (88W) 500 VAC @ 0.176A
DM) HT = 3.375 WT = 2.813 DT = 3.500 MD = 2.500 MW = 2.250 WEIGHT) 4 LBS

HEATH DX-100 PLATE HEATH P/N 54-30 POTTED TYPE
CORE) EI-150 X 2.5 STYLE #) 07 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 1830 VCT @ 400MA ICAS
DM) HT = 4.500 WT = 3.750 DT = 4.390 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

HEATH DX-100 PLATE OF OPEN FRAME VERSION
CORE) EI-175 X 2" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 1830 VCT @ 400MA ICAS
DM) HT = 5.250 WT = 4.375 DT = 4.205 MD = 3.125 MW = 3.500 WEIGHT) 14 LBS

HEATH DX-20 POWER MAIN POWER TRANSFORMER FOR HEATH DX-20
CORE) EI-125 X 1.75 STYLE #) 05 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 1200 VCT @ 120MA CCS
S2) 6.3 VAC @ 2A CCS
S3) 5.0 VAC @ 3A CCS
DM) HT = 3.750 WT = 3.125 DT = 3.875 MD = 2.750 MW = 2.500 WEIGHT) 6 LBS

HEATH DX-35/40 POWER TRANSFORMER
CORE) EI-125 X 1.75 STYLE #) 05 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 750-0-750 VAC @ 150MA ICAS (FWCT)
S2) 6.3 VAC @ 3.25A CCS
S3) 5.0 VAC @ 3A CCS
S4) 6.3 VAC @ 0.65A CCS
DM) HT = 3.750 WT = 3.125 DT = 3.875 MD = 2.750 MW = 2.500 WEIGHT) 6 LBS

HEATH DX-35/40 ER CASE EXACT REPLACEMENT IN ORIGINAL CASE
CORE) EI-125 X 1.75 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 750-0-750 VAC @ 150MA ICAS (FWCT)
S2) 6.3 VAC @ 3.25A CCS
S3) 5.0 VAC @ 3A CCS
S4) 6.3 VAC @ 0.65A CCS
DM) HT = 4.290 WT = 3.600 DT = 3.200 MD = 3.890 MW = 2.750 WEIGHT) 12 LBS

HEATH DX-60 POWER STYLE #6 HALFSHELL TYPE XFMR
CORE) EI-137 X 2" 29GA M6RH STYLE #) 06 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 260 VAC @ 500MA CCS
S2) 110 VAC @ 30MA CCS
S3) 6.3 VAC @ 2A CCS
DM) HT = 3.188 WT = 4.125 DT = 3.438 MD = 2.750 MW = 3.438 WEIGHT) 8 LBS

HEATH HA-10 SWINGING CHOKE P/N 46-28
CORE) EI-125 X 4.375 STYLE #) 06 E-I LAMINATED CORE
PR) 50 HY @ 50MA - 5 HY @ 450MA (1500 WVDC)
DM) HT = 5.250 WT = 3.750 DT = 3.125 MD = 2.500 MW = 3.125 WEIGHT) 13 LBS

HEATH HA-10 WARRIOR PLATE TO PRODUCE 1500 VDC @ 0.5A CCS FWCT
CORE) EI-175 X 4" 29GA M6RTM STYLE #) 06 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 3400 VCT @ 0.5A CCS (FWCT)
DM) HT = 5.250 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 25 LBS

HEATH HA-10 WARRIOR PLATE SP SPECIAL FOR FWCT CAPACITOR INPUT
CORE) EI-175 X 4" 29GA M6X STYLE #) 06 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 2500 VCT @ 0.7A CCS (FWCT)
DM) HT = 5.250 WT = 5.250 DT = 4.375 MD = 3.500 MW = 4.375 WEIGHT) 25 LBS

HEATH HA-14-X HEAVY DUTY OUTBOARD POWER TRANSFORMER
CORE) EI-162 X 3" 29GA M6X STYLE #) 02 E-I LAMINATED CORE
PR) 24 VCT 250 HZ (PP TRANSISTOR DRIVEN) S1) 0-2400-2800 VAC @ 0.5A CCS
S2) 120 VAC @ 0.1A CCS
DM) HT = 4.250 WT = 5.750 DT = 6.150 MD = 4.125 MW = 4.937 WEIGHT) 21 LBS

HEATH HL-2200 FILAMENT XFMR EXACT REPLACEMENT TRANSFORMER
CORE) EI-137 X 1.375 STYLE #) 05 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 5.0 VCT @ 30A CCS
S2) 90 VAC @ 0.1A CCS
DM) HT = 4.125 WT = 3.438 DT = 3.750 MD = 2.375 MW = 2.750 WEIGHT) 6 LBS

HEATH HO-10 SCOPE POWER XFMR HEATH P/N 54-105-24
CORE) EI-125 X 1.75 STYLE #) 02 E-I LAMINATED CORE
PR) 115/230 VAC 50/60 HZ 1 PH
S1) 0-325-650-1175-1175.625 @ 60MA, 5MA & 0.3A
S2) 120 VAC @ 60MA
S3) 6.3 VAC @ 0.6A
S4) 6.3 VCT @ 3.6A
DM) HT = 3.125 WT = 3.750 DT = 3.325 MD = 2.750 MW = 3.125 WEIGHT) 6 LBS

HEATH HO-13 & HO-10 MONITOR SCOPE POWER XFMR HEATH P/N 54-130
CORE) EI-100 X 1.5 STYLE #) 05 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 1200 VAC @ .005A CCS
S2) 0.625 VAC @ 0.3A CCS (5 KVDC INS)
S3) 220 VAC @ .050A CCS
S4) 6.3 VAC @ 0.6A CCS
S5) 6.3 VAC @ 3.6A CCS
DM) HT = 3.000 WT = 2.500 DT = 3.125 MD = 2.500 MW = 2.000 WEIGHT) 3 LBS

HEATH HP-23A/B POWER XFMR FOR HP-23A OR HP-23B POWER SUPPLY
CORE) EI-137 X 2.5" 29GA M6X STYLE #) 06 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 282 VAC @ 0.25A CCS
S2) 0-95-125 VAC @ 0.1A CCS
S3) 12.6 VCT @ 6A CCS
DM) HT = 3.437 WT = 4.125 DT = 3.437 MD = 2.750 MW = 3.437 WEIGHT) 10 LBS

HEATH HX-10 HD POWER MARAUDER P/N 54-114 STYLE #7 CASED UNIT
CORE) EI-162 X 3 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 940-407-111-0-111-407-940 VAC @ 375MA
S2) 6.3 VAC @ 9A CCS
S3) 5 VAC @ 3A CCS
S4) 5 VAC @ 3A CCS
DM) HT = 6.250 WT = 4.250 DT = 6.150 MD = 4.125 MW = 3.437 WEIGHT) 21 LBS

HEATH IO-102 SCOPE XFMR HEATH P/N 54-258
CORE) EI-137 X 2" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 120/240 VAC 50/60 HZ 1 PH
S1) 550 VAC @ 50MA CCS
S2) 200 VAC @ 100MA CCS
S3) 26 VAC @ 250 MA CCS
S4) 7.88 VAC @ 1A CCS (?)
S5) 0.35 VAC @ 1A CCS
DM) HT = 4.125 WT = 3.437 DT = 4.375 MD = 3.000 MW = 2.750 WEIGHT) 8 LBS

HEATH KL-1 FILAMENT XFMR PAIR 4-400A'S ** REWIND ONLY **
CORE) EI-125 X 2" 29GA M6RH6 STYLE #) 05 E-I LAMINATED CORE
PR) 115 VAC 60 HZ 1 PH
S1) 5.0 VAC @ 30A CCS (NO CT)
DM) HT = 3.750 WT = 3.125 DT = 4.125 MD = 3.000 MW = 2.500 WEIGHT) 7 LBS

HEATH OP-1 SCOPE
CORE) EI-125 X 2.625 STYLE #) 5 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 120 VAC @ 50MA (PURPLE)
S2) 180 VAC @ 300MA (RED)
S3) 6.6 VCT @ 3A (GREEN)
S4) 6.6 VAC @ 2A (BLUE)
S5) 0-1840-1841.35 (IMA)(@0.2A) (YELLOW)
DM) HT = 3.750 WT = 3.125 DT = 4.200 MD = 3.625 MW = 2.500 WEIGHT) 9 LBS

HEATH P/N 54-884 STEREO POWER AMPLIFIER POWER TRANSFORMER
CORE) EI-162 X 3.5" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 125 VCT @ 6A CCS (+ & - 91 VDC)
S2) 54 VCT @ 0.5A CCS (+15,-15,+12,+35 VDC)
S3) 6 VAC @ 0.5A CCS (METER LIGHTS)
DM) HT = 5.750 WT = 4.250 DT = 6.650 MD = 4.625 MW = 3.437 WEIGHT) 24 LBS

HEATH PS-23 DC CHOKE (L1) 6 HY @ 175 MA DC (350/275 VDC)
CORE) EI-100 X 1 STYLE #) 01 E-I LAMINATED CORE
PR) 6 HY @ 175 MA DC (350 WVDC)
DM) HT = 2.550 WT = 3.066 DT = 2.500 MD = 0.000 MW = 3.562 WEIGHT) 2 LBS

HEATH SB-1000 HD SPECIAL HIGHER VOLTAGE MODEL WITH FIL & LV WDNGS
CORE) EI-212 X 3" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 240 VAC 60 HZ 1 PH
S1) 0-1050-1150-1250-1350-1450-1550V @ 0.5A
S2) 5.2 VCT @ 15A CCS
S3) 10.5 VAC @ 0.5A CCS
DM) HT = 6.375 WT = 5.313 DT = 5.678 MD = 4.250 MW = 4.250 WEIGHT) 29 LBS

HEATH SB-1000 POWER XFMR HEATH P/N 54-1061
CORE) EI-175 X 3.5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 1100 VAC @ 0.5A CCS
S2) 5.2 VCT @ 15A CCS
S3) 10.5 VAC @ 0.5A CCS
DM) HT = 5.250 WT = 4.375 DT = 5.705 MD = 4.625 MW = 3.500 WEIGHT) 22 LBS

HEATH SB-200 T-1 MAIN POWER TRANSFORMER
CORE) EI-175 X 3" 29G M-6 STYLE #) 02 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 800 VAC @ 500MA CCS
S2) 6.3 VCT @ 8A CCS
S3) 120 VAC @ 0.1A CCS
DM) HT = 4.375 WT = 5.250 DT = 5.205 MD = 4.125 MW = 4.375 WEIGHT) 19 LBS

HEATH SB-200-X OUTBOARD FOR 6 EA 572B TUBES
CORE) A-0274/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 800 VAC @ 1.5A CCS
S2) 6.3 VCT @ 24A CCS
S3) 120 VAC @ 0.100A CCS
DM) HT = 7.875 WT = 7.825 DT = 7.063 MD = 3.625 MW = 4.875 WEIGHT) 37 LBS

HEATH SB-200-XJ OUTBOARD FOR 6 EA 572B TUBES, JAPANESE PRI
CORE) A-0274/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 100/200 VAC 60 HZ 1 PH
S1) 800 VAC @ 1.5A CCS
S2) 6.3 VCT @ 24A CCS
S3) 120 VAC @ 0.100A CC
DM) HT = 7.875 WT = 7.825 DT = 7.063 MD = 3.625 MW = 4.875 WEIGHT) 37 LBS

HEATH SB-200-1 HIGHER VOLTAGE MODEL
CORE) EI-175 X 3 STYLE #) 02 E-I LAMINATED CORE
PR) 110/220 VAC 60 HZ 1 PH
S1) 900 VAC @ 500MA CCS
S2) 6.3 VCT @ 8A CCS
S3) 120 VAC @ 0.1A CCS
DM) HT = 4.375 WT = 5.250 DT = 5.205 MD = 4.125 MW = 4.375 WEIGHT) 19 LBS

HEATH SB-200-800A7 SPECIAL XFMR FOR 3CX800A7 CONVERSION
CORE) EI-175 X 3" 29GA M6X STYLE #) 02 E-I LAMINATED CORE
PR) 120/240 VAC 60HZ 1 PH
S1) 1800 VAC @ 0.6A ICAS
S2) 13.5 VAC @ 1.5A CCS
S3) 120 VAC @ 0.15A CCS
DM) HT = 4.375 WT = 5.250 DT = 5.205 MD = 4.125 MW = 4.375 WEIGHT) 19 LBS

HEATH SB-220 FIL XFMR 50 HZ EXACT REPLACEMENT TRANSFORMER
CORE) EI-137 X 1.375 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 120/240 VAC 50 HZ 1 PH
S1) 5.0 VCT @ 30A CCS
S2) 90 VAC @ 0.1A CCS
DM) HT = 3.438 WT = 4.125 DT = 3.108 MD = 2.750 MW = 2.375 WEIGHT) 6 LBS

HEATH SB-220 FILAMENT XFMR EXACT REPLACEMENT TRANSFORMER
CORE) EI-137 X 1.375 STYLE #) 05 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 5.0 VCT @ 30A CCS
S2) 90 VAC @ 0.1A CCS
DM) HT = 3.438 WT = 4.125 DT = 3.108 MD = 2.750 MW = 2.375 WEIGHT) 6 LBS

HEATH SB-220-X 2-3 TUBE OUTBOARD POWER TRANSFORMER
CORE) A-0480/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH WITH HI-LO TAPS
S1) 925/1175 VAC @ 2.13A CCS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS

HEATH SB-220-X2 OUTBOARD POWER TRANSFORMER (4-6 3-500Z)
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH WITH HI-LO TAPS
S1) 925/1175 VAC @ 3.5A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HEATH SB-220-X2B USE WITH FULL WAVE BRIDGE RECTIFIER
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH WITH HI-LO TAPS
S1) 0-1850-2400 VAC @ 1.75A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HEATH SB-220-X2BS X2 FOR BRIDGE RECT WITH HI/LO SEC TAPS
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 230 VAC 60 HZ 1 PH
S1) 0-1850-2400 VAC @ 2.0A CCS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HEATH SB-220-3-7 EXTRA HD REPLACEMENT WITH 7 MIL C-CORE
CORE) B-0393/ (SIDE MOUNT) STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH HI-LO TAPS
S1) 860/1171 VAC @ 1.3A CCS
DM) HT = 6.000 WT = 6.325 DT = 6.281 MD = 3.625 MW = 4.000 WEIGHT) 23 LBS

HEATH SB-220-3-7-NHL EX HD XFMR: 7 MIL CORE & HI PRI TAP ONLY
CORE) B-0393/ SIDE MOUNT STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH
S1) 860/1171 VAC @ 1.3A CCS
DM) HT = 6.000 WT = 6.325 DT = 6.281 MD = 3.625 MW = 4.000 WEIGHT) 23 LBS

HEATH SB-221 HEAVY DUTY REPLACEMENT TRANSFORMER
CORE) A-0393/ (SIDE MOUNT) STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH HI-LO TAPS
S1) 860/1171 VAC @ 1.0A CCS
DM) HT = 6.000 WT = 6.325 DT = 6.281 MD = 3.625 MW = 4.000 WEIGHT) 23 LBS

HEATH SB-221-X 2-3 TUBE OUTBOARD POWER TRANSFORMER
CORE) A-0480/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 117/234 VAC 60 HZ 1 PH WITH HI-LO TAPS
S1) 925/1175 VAC @ 2.13A CCS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS

HEATH SB-230 POWER PLATE, BIAS, & FIL POWER FOR 8873
CORE) EI-150 X 3 STYLE #) 05 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 800 VAC @ 0.4A CCS
S2) 95 VAC @ 0.045A CCS
S3) 6.3 VAC @ 3.5A CCS
DM) HT = 4.500 WT = 3.750 DT = 5.375 MD = 4.000 MW = 3.000 WEIGHT) 14 LBS

HEATH SB-230-HD POWER PLATE, BIAS, & FIL POWER FOR 2 EA 8873
CORE) EI-150 X 5" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 1100 VAC @ 0.4A CCS
S2) 95 VAC @ 0.045A CCS
S3) 12.6 VCT @ 4A CCS
DM) HT = 4.500 WT = 3.750 DT = 6.890 MD = 6.000 MW = 3.000 WEIGHT) 23 LBS

HEATH SB-610 SCOPE XFMR P/N 54-168, T-601 MONTIOR SCOPE POWER
CORE) EI-100 X 1.5 STYLE #) 05 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 600 VAC @ 0.020A CCS
S2) 215 VAC @ 0.050A CCS
S3) 6.3 VAC @ 1.5A CCS (5 KVDC TEST)
S4) 6.3 VAC @ 2.5A CCS
DM) HT = 3.000 WT = 2.500 DT = 3.125 MD = 2.500 MW = 2.000 WEIGHT) 3 LBS

HEATH SB-614 SCOPE XFMR P/N 54-182, STATION MONTIOR SCOPE POWER
CORE) EI-100 X 1.5" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 600 VAC @ 0.020A CCS
S2) 210 VAC @ 0.050A CCS
S3) 6.3 VAC @ 0.6A CCS (5 KVDC TEST)
S4) 6.3 VAC @ 0.6A CCS (16 VDC @ 55 MA)
DM) HT = 3.000 WT = 2.500 DT = 3.125 MD = 2.500 MW = 2.000 WEIGHT) 3 LBS

HEATH SCOPE P/N 54-25
CORE) EI-II2 X 1.5 STYLE #) 05 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 0-390-780 @ 80MA
S2) 780-1440 @ 3MA
S3) 1440-1440.625 @ 600MA
S4) 6.3 VAC @ 3.5A
S5) 6.3 VAC @ 0.6A
DM) HT = 3.375 WT = 2.813 DT = 2.918 MD = 2.500 MW = 2.250 WEIGHT) 4 LBS

HEATH TX-1 APACHE PLATE HEATH P/N 54-30 POTTED-CUST.SUPPLY CASE
CORE) EI-150 X 2.5 STYLE #) 07 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 1830 VCT @ 400MA ICAS
DM) HT = 4.500 WT = 3.750 DT = 4.390 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

HEATH TX-1 LV POWER APACHE (54-65)
CORE) EI-150 X 2.5 STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 300-120-0-120-300 VAC 175MA
S2) 5.0 VAC @ 4A
S3) 6.3 VAC @ 3.5A
S4) 6.3 VAC @ 9.0A
S5) 5.0 VAC @ 2.0A
DM) HT = 4.500 WT = 3.750 DT = 4.390 MD = 3.500 MW = 3.000 WEIGHT) 12 LBS

HEATH TX-1 MODULATION APACHE HEATH TX-1 APACHE MOD XFMR P/N 51-43
CORE) EI-175 X 2 STYLE #) 04 E-I LAMINATED CORE
PR) 11,000 OHMS P-P CT
S1) 0-500-3000 OHMS @ 250MA DC (175 WATTS)
DM) HT = 5.250 WT = 4.375 DT = 4.205 MD = 3.125 MW = 3.500 WEIGHT) 14 LBS

HEATH VHF-1 SENECA POWER P/N 54-73
CORE) EI-150 X 2" 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 1600 VCT @ 150MA CCS
S2) 800 VCT @ 100MA CCS
S3) 5.0 VAC @ 2A CCS
S4) 5.0 VAC @ 2A CCS
S5) 6.3 VAC @ 8A CCS
DM) HT = 4.500 WT = 3.750 DT = 4.375 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

HEATH W4-AM POWER XFMR P/N 54-29, REWOUND IN ORIGINAL CASE
CORE) EI-150 X 1.5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 120 VAC 60 HZ 1 PH
S1) 760 VCT @ 130MA CCS
S2) 5.0 VAC @ 3A CCS
S3) 6.3 VCT @ 4A CCS
DM) HT = 0.000 WT = 3.750 DT = 3.390 MD = 2.500 MW = 3.000 WEIGHT) 8 LBS

HEATH W5M POWER P/N 54-32 P/N 54-32, REWOUND IN ORIGINAL CASE
CORE) EI-150 X 2" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 117 VAC 60 HZ 1 PH
S1) 900 VCT @ 140MA CCS
S2) 5.0 VAC @ 3A CCS
S3) 6.3 VCT @ 4A CCS
DM) HT = 0.000 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

HENRY TEMPO 2000
CORE) EI-175 X 4" 29GA M6X STYLE #) 02 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH HI/LO TAPS
S1) 980/760 VAC @ 1.0A ICAS
DM) HT = 4.375 WT = 5.250 DT = 6.205 MD = 5.125 MW = 4.375 WEIGHT) 25 LBS

HENRY TEMPO 2020 T101 ON SCHEMATIC
CORE) A-36 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-100-110-117/0-100-110-117 VAC 60 HZ 1 PH
S1) 330 VAC @ 0.5A CCS
S2) 0-80-250 VAC @ 100MA CCS
S3) 0-10-20-23 VAC @ 6A (13.8 VDC PRI)
S4) 4.5 VCT @ 250MA CCS (BASE FEEDBACK)
DM) HT = 4.563 WT = 4.700 DT = 3.875 MD = 2.375 MW = 2.500 WEIGHT) 7 LBS

HENRY TEMPO 2020 (C) T101 ON SCHEMATIC -- 117 VAC PRI ONLY
CORE) A-36 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 117 VAC 60 HZ 1 PH
S1) 330 VAC @ 0.5A CCS
S2) 0-80-250 VAC @ 100MA CCS
S3) 0-10-20-23 VAC @ 6A (13.8 VDC PRI)
S4) 4.5 VCT @ 250 MA CCS (BASE FEEDBACK)
DM) HT = 4.563 WT = 4.700 DT = 3.875 MD = 2.375 MW = 2.500 WEIGHT) 7 LBS

HENRY 1KD-5 POWER XFMR T1, P/N ECA-1111, DIRECT REPLACEMENT
CORE) EI-175 X 3" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 2250 VAC @ 200MA CCS
S2) 5.0 VCT @ 15A CCS
DM) HT = 5.250 WT = 4.375 DT = 5.205 MD = 4.125 MW = 3.500 WEIGHT) 19 LBS

HENRY 1KD-5X OUTBOARD POWER TRANSFORMER
CORE) A-480 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 115/230 VAC 50/60 HZ 1 PH
S1) 2250 VAC @ 0.7A CCS
S2) 5.0 VCT @ 15A CCS
DM) HT = 8.375 WT = 8.075 DT = 7.688 MD = 3.937 MW = 5.500 WEIGHT) 46 LBS

HENRY 2K CHOKE RESONATES WITH 0.1 MFD 7500 VDC CAP
CORE) EI-175 X 4" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 17.6 HY @ 500MA CCS (700 MA ICAS)
DM) HT = 5.250 WT = 4.375 DT = 6.205 MD = 5.125 MW = 3.500 WEIGHT) 25 LBS

HENRY 2K CLASSIC
CORE) EI-250 X 3.125 STYLE #) 04 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 0-2700-3600 VAC @ 0.5A
S2) 10 VCT @ 15A
DM) HT = 7.500 WT = 6.250 DT = 6.275 MD = 4.250 MW = 5.500 WEIGHT) 42 LBS

HENRY 2K CLASSIC DC CHOKE L101 HEAVY DUTY REPLACEMENT FOR ECA 5023
CORE) EI-162 X 2.5" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 8 HY @ 0.8A DC (0.1 MFD 7.5 KVDC CAP)
DM) HT = 5.750 WT = 4.250 DT = 5.650 MD = 3.625 MW = 3.437 WEIGHT) 18 LBS

HENRY 2K FILAMENT BIAS
CORE) EI-150 X 2 STYLE #) 04 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 5.5 VCT @ 30A S2) 90 VAC @ 0.1A
DM) HT = 4.500 WT = 3.750 DT = 3.890 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS

HENRY 2K PLATE TRANSFORMER EXACT REPLACEMENT IN STEEL CASE
CORE) EI-19 X 3.5" 29GA M6X STYLE #) 07 E-I LAMINATED CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 6000 VCT @ 0.5A CCS (FWCT)
DM) HT = 8.375 WT = 4.750 DT = 7.910 MD = 4.625 MW = 3.875 WEIGHT) 34 LBS

HENRY 2K ULTRA

CORE) EI-212 X 4 STYLE #) 04 E-I LAMINATED CORE

PR) 115/230 VAC 60 HZ 1 PH

S1) 2400 VRMS @ 0.45A CCS

S2) 0--6.3--18 VAC @ 6.4A/2A CCS

DM) HT = 6.375 WT = 5.313 DT = 6.678 MD = 5.250 MW = 4.250 WEIGHT) 38 LBS

HENRY 2K-2 MODIFIED

CORE) A-0518/ C-CORE STYLE #) 09 HIPERSIL C-CORE

PR) 120/240 VAC 60 HZ 1 PH

S1) 3500 VAC @ 0.8A CCS

S2) 10.2 VCT @ 15A CCS

DM) HT = 9.244 WT = 6.656 DT = 5.563 MD = 4.500 MW = 6.000 WEIGHT) 38 LBS

HENRY 2K-2 POWER HIPERSIL CORE TYPE REPLACEMENT XFMR

CORE) A-0480/ C-CORE STYLE #) 09 HIPERSIL C-CORE

PR) 120/240 VAC 60 HZ 1 PH

S1) 3500 VAC @ 0.4A ICAS

S2) 10.2 VCT @ 15A CCS

DM) HT = 8.344 WT = 6.125 DT = 5.000 MD = 3.937 MW = 4.500 WEIGHT) 26 LBS

HENRY 2K-3 DC FILTER CHOKE 17.6 HY @ 0.050A TO 10 HY @ 0.7A DC

CORE) EI-19 X 2 STYLE #) 04 E-I LAMINATED CORE

PR) 17.6 HY @ 0.050A DC TO 10 HY @ 0.7A DC

DM) HT = 7.000 WT = 4.750 DT = 6.410 MD = 3.250 MW = 3.875 WEIGHT) 22 LBS

HENRY 2K-3/4 ER PLATE EXACT REPLACEMENT POWER TRANSFORMER

CORE) EI-250 X 3.125 STYLE #) 04 E-I LAMINATED CORE

PR) 115/230 VAC 60 HZ 1 PH

S1) 3500 VAC @ 0.4A CCS

S2) 10.2 VCT @ 15A CCS

DM) HT = 7.500 WT = 6.250 DT = 6.275 MD = 4.250 MW = 5.500 WEIGHT) 42 LBS

HENRY 2K-3/4 PLATE HEAVY DUTY HIPERSIL CORE TRANSFORMER

CORE) A-518 C-CORE STYLE #) 09 HIPERSIL C-CORE

PR) 115/230 VAC 60 HZ 1 PH

S1) 3500 VAC @ 0.6A CCS

S2) 10.2 VCT @ 15A CCS

DM) HT = 9.994 WT = 6.656 DT = 5.563 MD = 4.500 MW = 6.000 WEIGHT) 38 LBS

HENRY 2K-3/4-1 PLATE HD HIPERSIL XFMR WITH HI/LO SEC TAP

CORE) A-518 C-CORE STYLE #) 09 HIPERSIL C-CORE

PR) 115/230 VAC 60 HZ 1 PH

S1) 0-3000-3500 VAC @ 0.6A CCS

S2) 10.2 VCT @ 15A CCS

DM) HT = 9.994 WT = 6.656 DT = 5.563 MD = 4.500 MW = 6.000 WEIGHT) 38 LBS

HENRY 2K-4 CHOKE EXACT REPLACEMENT (USE WITH 0.1 MFD CAP)

CORE) EI-175 X 4 29GA M6X STYLE #) 04 E-I LAMINATED CORE

PR) 10.0 HY @ 500MA CCS (700 MA ICAS)

DM) HT = 5.250 WT = 4.375 DT = 6.205 MD = 5.125 MW = 3.500 WEIGHT) 25 LBS

HENRY 2K-4-XM SPECIAL OUTBOARD POWER TRANSFORMER

CORE) A-516 C-CORE STYLE #) 10 HIPERSIL C-CORE

PR) 120/240 VAC 60 HZ 1 PH

S1) 3500 VAC @ 1A CCS

S2) 10.2 VCT @ 30A

DM) HT = 9.125 WT = 8.825 DT = 8.825 MD = 4.500 MW = 6.250 WEIGHT) 58 LBS

HENRY 2K-4-1 SPECIAL OUTBOARD POWER TRANSFORMER
CORE) A-518 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 4500 VAC @ 800MA
S2) 10.2 VCT @ 15A
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HENRY 2KD-2 POWER XFMR T1, P/N 70398, DIRECT REPLACEMENT
CORE) EI-212 X 3" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 2800 VAC @ 400MA CCS
S2) 10.0 VCT @ 15A CCS
DM) HT = 6.375 WT = 5.313 DT = 5.678 MD = 4.250 MW = 4.250 WEIGHT) 29 LBS

HENRY 2KD-5 POWER XFMR T1, P/N FDN-7497, DIRECT REPLACEMENT
CORE) EI-212 X 3" 29GA M6X STYLE #) 04 E-I LAMINATED CORE
PR) 115/230 VAC 60 HZ 1 PH
S1) 0-1780-2250 VAC @ 400MA CCS
S2) 10.0 VCT @ 15A CCS
DM) HT = 6.375 WT = 5.313 DT = 5.678 MD = 4.250 MW = 4.250 WEIGHT) 29 LBS

HENRY 3K ER PLATE EXACT REPLACEMENT, TRIAD P/N 70400
CORE) EI-250 X 5" 29GM6XRH STYLE #) 04 E-I LAMINATED CORE
PR) 230 VAC 60 HZ 1 PH HI-LO TAP
S1) 3800/2800 VAC @ 600MACCS
DM) HT = 8.250 WT = 6.250 DT = 8.150 MD = 7.000 MW = 5.000 WEIGHT) 65 LBS

HENRY 3K-A DC FILTER CHOKE RESONATES WITH 0.1 MFD 7500V CAPACITOR
CORE) A-0203/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 10 HY @ 700MA DC
DM) HT = 7.500 WT = 5.906 DT = 4.500 MD = 3.375 MW = 4.112 WEIGHT) 17 LBS

HENRY 3K-A ER DC CHOKE 804CT REPLACEMENT (USE WITH 0.1 MFD CAP)
CORE) EI-175 X 4 STYLE #) 04 E-I LAMINATED CORE
PR) 10.0 HY @ 500MA CCS (700 MA ICAS)
DM) HT = 5.250 WT = 4.375 DT = 6.205 MD = 5.125 MW = 3.500 WEIGHT) 25 LBS

HENRY 3K-A PLATE HIPERSIL REPLACEMENT FOR HENRY 3K-A
CORE) A-0518/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 230 VAC 60 HZ 1 PH HI-LO TAP
S1) 4000/3000 VAC @ 600MA CCS
DM) HT = 9.250 WT = 6.656 DT = 5.563 MD = 4.500 MW = 6.000 WEIGHT) 38 LBS

HENRY 3K-A-M HEAVY DUTY PLATE TRANSFORMER
CORE) A-516 C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 230 VAC 60 HZ 1 PH HI-LO TAPS
S1) 4000/3000 VAC @ 1.0A CCS
DM) HT = 9.125 WT = 8.825 DT = 8.825 MD = 4.500 MW = 6.250 WEIGHT) 58 LBS

HENRY 3K-A-MC PLATE SPECIAL HENRY 3K-A PLATE WITH SEC TAPS
CORE) A-0518/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 230 VAC 60 HZ 1 PH
S1) 0-2800-3500-4000 VAC @ 0.6A CCS
DM) HT = 9.244 WT = 6.656 DT = 5.563 MD = 4.500 MW = 6.000 WEIGHT) 38 LBS

HENRY 3K-CLASSIC X PLATE XFMR FOR EXPORT MODEL
CORE) A-0525/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-200-210-220-230 VAC 60 HZ 1 PH
S1) 0-3000-4000 VAC @ 1.5A ICAS
DM) HT = 9.769 WT = 9.825 DT = 9.188 MD = 5.000 MW = 6.437 WEIGHT) 86 LBS

HENRY 3002A-M PLATE HEAVY DUTY PLATE TRANSFORMER
CORE) A-0516/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-230-240 VAC 60 HZ 1 PH
S1) 0-3000-4400 VAC @ 1.0A CCS
DM) HT = 9.125 WT = 8.765 DT = 7.475 MD = 4.500 MW = 6.250 WEIGHT) 58 LBS

HENRY 4K ULTRA CHOKE
CORE) EI-212 X 4 STYLE #) 04 E-I LAMINATED CORE
PR) 4 HY @ 1.5A CCS OR 2.0A ICAS
DM) HT = 6.375 WT = 5.313 DT = 6.678 MD = 5.250 MW = 4.250 WEIGHT) 38 LBS

HENRY 4K ULTRA DC CHOKE RESONANT CHOKE WITH 0.2 MFD 10 KVDC CAP
CORE) A-0518/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 9.0 HY @ 1.0A DC (4500 WVDC)
DM) HT = 9.244 WT = 6.656 DT = 5.563 MD = 4.500 MW = 6.000 WEIGHT) 38 LBS

HENRY 4K ULTRA PLATE SPECIAL XFMR WITH 75% PRI CUTBACK TAP
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-294 VAC 60 HZ 1 PH
S1) 0-4200-5000 VAC @ 1.0A ICAS
DM) HT = 10.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HENRY 4K ULTRA PLATE (-1) SPECIAL XFMR WITH 75% PRI CUTBACK TAP
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-220-294 VAC 60 HZ 1 PH
S1) 0-4200-5000 VAC @ 1.0A ICAS
DM) HT = 9.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HENRY 4K ULTRA PLATE (-2) 230, 240, 250 VAC & 75% PRI CUTBACK TAP
CORE) A-0518/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) 0-230-240-250-294 VAC 60 HZ 1 PH
S1) 0-4200-5000 VAC @ 1.0A ICAS
DM) HT = 9.000 WT = 8.825 DT = 8.313 MD = 4.500 MW = 6.250 WEIGHT) 66 LBS

HENRY 4K-2 DC FILTER CHOKE REPLACES TRIAD P/N 16113
CORE) EI-175 X 4" 29GA M6X STYLE #) 02 E-I LAMINATED CORE
PR) 8.8 HY @ 0.7A DC (RESONATE WITH 0.2 MF)
DM) HT = 4.375 WT = 5.250 DT = 6.205 MD = 5.125 MW = 4.375 WEIGHT) 25 LBS

HENRY 8K ULTRA OUTBOARD HEAVY DUTY OUTBOARD PLATE TRANSFORMER
CORE) A-0540/ C-CORE STYLE #) 10 HIPERSIL C-CORE
PR) +10,0,-10,208,240 VAC 60 HZ 1 PH
S1) 0-4500-6000 VAC @ 2.0A CCS
DM) HT = 14.000 WT = 11.950 DT = 10.125 MD = 5.625 MW = 7.500 WEIGHT) 164 LBS

HENRY 8K ULTRA XHD DC CHOKE EXTRA HEAVY DUTY DC FILTER CHOKE
CORE) A-0525/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 8.0 HY @ 1.5A CCS
DM) HT = 9.769 WT = 7.469 DT = 6.063 MD = 5.000 MW = 5.750 WEIGHT) 49 LBS

HUNTER 2000A POWER TRANSFORMER
CORE) A-0459/ C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 0-450-700-900 VAC @ 1.0A CCS
S2) 6.3 VCT @ 16A CCS
S3) 6.3 VAC @ 1A CCS
DM) HT = 5.250 WT = 5.875 DT = 6.600 MD = 6.000 MW = 4.000 WEIGHT) 23 LBS

HUNTER 2000B POWER TRANSFORMER
CORE) A-459 C-CORE STYLE #) 09 HIPERSIL C-CORE
PR) 120/240 VAC 60 HZ 1 PH
S1) 0-800-860-920 VAC @ 1.0A CCS
S2) 6.3 VCT @ 16A CCS
S3) 6.3 VAC @ 1A CCS
DM) HT = 5.250 WT = 5.875 DT = 6.600 MD = 6.000 MW = 4.000 WEIGHT) 23 LBS

HUNTER 2000C POWER TRANSFORMER
CORE) EI-225S X 3" STYLE #) 06 E-I LAMINATED CORE
PR) 117/234 VAC 60 HZ 1 PH
S1) 900 VAC @ 1.0A CCS
S2) 7.0 VAC @ 1.0A CCS
S3) 6.0 VCT @ 25A CCS
DM) HT = 6.500 WT = 7.062 DT = 6.031 MD = 4.781 MW = 5.812 WEIGHT) 35 LBS

HY-GAIN 3750 POWER XFMR STYLE NO. 5 HORIZONTAL ENDBELL TYPE
CORE) EI-150 X 2 29GA M6X STYLE #) 05 E-I LAMINATED CORE
PR) 0-100-110-120/0-100-110-120 VAC 60HZ 1 PH
S1) 0-265-530 VAC @ 0.25A CCS
S2) 0-130-260 VAC @ 0.1A CCS
S3) 80 VAC @ 0.1A CCS
S4) 0-7-14 VAC @ 3.5A CCS
S5) 6.3 VAC @ 4.5A CCS
S6) 12.6 VAC @ 0.7A CCS
DM) HT = 4.500 WT = 3.750 DT = 4.375 MD = 3.000 MW = 3.000 WEIGHT) 10 LBS